

DAO PHAY NGÓN CARBIDE 3 ME PHÁ THÔ TUNGSTEN CARBIDE 3 FLUTES ROUGHING END MILLS


RIGHT-HAND ROTATION / LEFT-HAND ROTATION - UP CUT



Type 1



Type 2



LOWER FINISHING


RIGHT-HAND ROTATION / LEFT-HAND ROTATION - DOWN CUT



Type 3



Type 4



UPPER FINISHING

3 flute spiral router. For CNC machines and for portable routers. For wood, plastic material.
Feed rates range from 2 – 16 m/min of 18000 - 24000 RPM. Roughing operations

CODE Type 1	CODE Type 2	CODE Type 3	CODE Type 4	Cut diameter ĐK chuôi cắt	Flute length Chiều dài cắt l	Total length Tổng chiều dài L	Shank diameter ĐK chuôi D
131-3080-22	132-3080-22	133-3080-22	134-3080-22	8	22	70	8
131-3080-32	132-3080-32	133-3080-32	134-3080-32	8	32	80	8
131-3100-32	132-3100-32	133-3100-32	134-3100-32	10	32	80	10
131-3100-42	132-3100-42	133-3100-42	134-3100-42	10	42	90	10
131-3100-52	132-3100-52	133-3100-52	134-3100-52	10	52	100	10
131-3120-32	132-3120-32	133-3120-32	134-3120-32	12	32	80	12
131-3120-42	132-3120-42	133-3120-42	134-3120-42	12	42	90	12
131-3120-52	132-3120-52	133-3120-52	134-3120-52	12	52	100	12
131-3140-42	132-3140-42	133-3140-42	134-3140-42	14	42	90	14
131-3140-52	132-3140-52	133-3140-52	134-3140-52	14	52	100	14
131-3160-32	132-3160-32	133-3160-32	134-3160-32	16	32	80	16
131-3160-42	132-3160-42	133-3160-42	134-3160-42	16	42	90	16
131-3160-52	132-3160-52	133-3160-52	134-3160-52	16	52	100	16
131-3160-62	132-3160-62	133-3160-62	134-3160-62	16	62	110	16
131-3180-52	132-3180-52	133-3180-52	134-3180-52	18	52	100	18
131-3180-72	132-3180-72	133-3180-72	134-3180-72	18	72	120	18
131-3200-52	132-3200-52	133-3200-52	134-3200-52	20	52	100	20
131-3200-72	132-3200-72	133-3200-72	134-3200-72	20	72	120	20
131-3200-102	132-3200-102	133-3200-102	134-3200-102	20	102	150	20
131-3250-52	132-3250-52	133-3250-52	134-3250-52	25	52	100	25
131-3250-102	132-3250-102	133-3250-102	134-3250-102	25	102	150	25